

TEST RESULTS

| THERMAL TEST RESULTS - SANS 204 | | MECHANICAL PERFORMANCE TEST RESULTS - SANS 613 | |
|---------------------------------|-------------|--|----------------|
| DESCRIPTION | RESULTS | DESCRIPTION RESULTS | |
| U-VALUE | 5.73 W/m²/K | NEGATIVE PRESSURE | Passed I500 PA |
| SHGC | 0.33 | POSITIVE PRESSURE | Passed I500 PA |
| DESIGN WIND LOAD | 2000 PA | WATER PENETRATION | Passed 300 PA |
| 6.38 mm Laminated Safety Glass | | STRUCTURAL | Passed 2250 PA |

Test results are based on a specific window size and configuration and results will differ for different window sizes and configurations.

APPLICATIONS


| HOME | MANSION | MALL | ∭ ⊞ TOWER |
|------|-----------|--------------|-------------------|
| √ | √ | | |
| | √ | √ | √ |
| | √ | | |
| √ | √ | √ | √ |
| | √ | √ | |
| | √ | √ | |
| | √ | | √ |
| | √ | | √ |
| | HOME √ | HOME MANSION | HOME MANSION MALL |

To find your nearest Crealco Distribution Partner, please visit the Crealco website at: www.crealco.co.za

This brochure must be read in conjunction with the Installation, Cleaning & Maintenance Guidelines for the relevant system.

The manuals must also be used in conjunction with the design and cutting lists from the latest version of StarFront.











The Crealco Clip 44 Suite is the most extensive and versatile shopfront system from Wispeco. The system not only allows for various options on sliding, hinged or pivot doors, but also automated doors. Windows with multi-locking points are available to suit both domestic and commercial developments. With the wide range of available profiles, the Clip 44 can meet most requirements and is thermally efficient and weather proof.

FEATURES

- Comprehensive range of configurations available for both flush glazing and conventional shopfronts.
- Accommodates both hinged and sliding doors, as well as a wide range of different window types.
- Louvres, insect screens and safety bars can be incorporated into the system.
- Detailed documentation for manufacturing and maintenance available.

GLAZING

- Allows for easy replacement of a profile or glass panel.
- Accommodates single glazing panels from 4 mm to 12.38 mm and double glazing SIG units up to 25 mm.

GASKET & SEALS

- Specially designed high quality colour coded gaskets for ease of glass installation.
- Unique push-in gaskets ensures ease of manufacturing and replacement of old gaskets.

FINISH

Available in a variety of popular architectural powder coating and anodising colours and finishes.

HARDWARE

- A wide range of high quality hardware is locally available.
- Crealco components are well-priced and tested for the South African market.
- The Clip 44 is versatile and suits most locks and handles.





This brochure must be read in conjunction with the Installation, Cleaning & Maintenance Guidelines for the relevant system

The manuals must also be used in conjunction with the design and cutting lists from the latest version of StarFront

This brochure must be read in conjunction with the Installation, Cleaning & Maintenance Guidelines for the relevant system

The manuals must also be used in conjunction with the design and cutting lists from the latest version of StarFront.

Disclaimer: The right to make alterations is reserved © 2016 Wispeco (Pty) Ltd, All Rights Reserved Disclaimer: The right to make alterations is reserved © 2016 Wispeco (Pty) Ltd, All Rights Reserved July 2018